

# Simple & Dependable

# PHYTOTRONICS 1626D



## THE WORKHORSE OF PROPAGATION GREENHOUSES

Simple • Dependable • Effective

### 6 ZONES OF VARIABLE "AT A GLANCE" MISTING CONTROL

#### 6 ZONES OF CONTROL

One zone at a time, not to exceed 20 watts per zone.

#### ONE ZONE OPERATION

The system is designed so that no more than one zone will be in operation at a time.

#### VARIABLE MISTING TIME PER ZONE

"On" time settings can be set at 2, 4, 6, 8, 10, 12, 15 or 20 seconds.

#### INCREASED FLEXIBILITY

The "System Control Switch" multiplies all times shown on the controller by 1, 2 or 3X.

#### MANUAL OVERRIDE

Each zone can be turned on or off as long as desired.

#### SOLID STATE CIRCUITRY

Other than time switches, there are no moving parts to wear out.

#### AUTOMATIC OR MANUAL CONTROL AVAILABLE

The controller can be wired to a 24-hour timer or Photoelectric Control to turn the controller on in the morning and off in the evening.

#### EASY TO INSTALL & OPERATE

Complete wiring diagram with instructions included with each controller.

#### SMALL AND COMPACT

The controller measures 9½" wide x 7½" tall x 3" deep and weighs only 2.5 lbs.

#### INDICATOR LAMPS

Lights tell "at a glance" what zone is in operation and power is on 1x, 2x or 3x.

#### SAFE OPERATION

The misting controller has 24-volt AC output for safe greenhouse operation.

#### ACCURATE & TROUBLE-FREE

The Phytotronics Misting Controller was designed specifically for the horticultural industry.

*The 1626D is backed by a 1-year warranty as well as a loaner policy. The warranty and the loaner policy work together to make the Phytotronics 1626D one of the most serviceable and valuable misting controllers on the market today. Contact your local distributor for ordering or additional information.*

Manufactured by:



Distributed by:

13688 Rider Trail North, Earth City MO 63045  
Phone 314-770-0717 • Fax 314-506-4587  
www.phytotronics.com • sales@phytotronics.com